

Double Multimedia Flash to DVD Duplicator 1 to 6



Rating: Not Rated Yet

[Ask a question about this product](#)

Double multimedia Flash to DVD Duplicator

Main features of the Double Multimedia Flash to DVD Duplicator 1-7 (uPRO1-7)

- Disc to Disc? Disc copy to Disc
- Disc to USB/Flash? Multi-source append copy to USB/Flash
- USB/Flash to Disc? Multi-source append copy to disc
- USB/Flash to USB/Flash? Multi-source append copy to one USB/Flash



- [Product Description](#)
- [Features](#)
- [Specification](#)
- [Video](#)

Product Description

uPRO is an outstanding equipment which can solve the trouble of backing up disc and flash. Friendly user interface, uPRO can help you easily backup or transfer your disc or flash source to disc/flash target. The easiest way to collect your favorite discs into an USB/Flash storage.


- Support M-Disc which can protect data from damage for a thousand years.

- 4 copy functions in one unit. Easy to backup or transfer your disc/flash source to disc/flash target.
- Support Disc to USB/Flash appends copy. Load different discs one by one into the reader drive, and append copy to one USB/Flash target.
- Standalone, no PC required.
- Support SD, CF, SDHC, MicroSD source or target via USB card reader.
- Support USB/Flash multisession copy to disc.
- Support USB/Flash to append copy.

Features


• Disc to USB/Flash

1TB USB HDD can save up to 1,000 CD Discs.




• USB/Flash to Disc

Multi - Source append copy to one USB / Flash




• USB/Flash to USB/Flash

Multi - Source append copy to one USB / Flash



• Disc to Disc

1 to 1 Disc duplication



Specification

		Model	uPRO1-7
		Target	7
		Buffer (DDR2)	64MB
		Interface	SATA
		CD Speed	48X
		DVD Speed	16X
		Blu-ray Speed	10X
		Writing Method	DAO, TAO, RAW
		Disc Format Support	BD-ROM, BD-R, BD-RE /DVD-ROM, DVD-Video, DVD-Audio, Dual Layer DVD±R/ CD-ROM, CD-RW, CD-I, Audio CD, VCD, Mixed-mode CD, Multi-session CD/ CD-Extra, BOM
		Display	2x16 Backlight Monochrome
		Input	4 push buttons (Forward, Backward, Stop, Eject)
		Language Support	Chinese, English, Spanish, Portuguese, Japanese
Humidity	Operating		20%~80%
	Storage		5%~95%
Temperature	Working		5°C ~ 45°C
	Storage		-20°C ~ 85°C
Controller Power	Voltage		12V,5V
Consumption	Current		3A Max
Safety			FCC, CE, RoHS

Video